



Maps



CAD & Technical Drawings



Photographs



Graphic Art

Colortrac SmartLF Gx+ 42/Gx+ T42

Professional SmartLF Scanning Solutions for:

REPROGRAPHICS | COPY SHOPS | GRAPHICS DESIGNERS

MAPPING & GIS PROFESSIONALS | AEC CAD DRAWING OFFICES



- ▶ Unique 2D LED¹ illumination system – instant-on, long-life, no fluorescent tubes
- ▶ Full high definition (HD) 1200dpi optical CCD² resolution – the highest on the market
- ▶ ENERGY STAR[®] qualified – uses 30% less power and 94% less when idle – cuts costs
- ▶ High productivity – scan A0/E-size documents FAST at 12ips @ 200dpi mono and 4ips color
- ▶ Optional ScanWorks³ software offers outstanding "scan once interactive 2D image restoration"
- ▶ 42" image width, 46" document width - ideal for A0, E and architectural E-size document scanning
- ▶ Combines faithful 48-bit color graphics capture with crisp, sharp line definition for maximum capability
- ▶ Motorized thick media option for board mounted originals up to 0.8"/20mm in Gx+ T42
- ▶ Network-ready – Gigabit Ethernet connectivity using unlimited LAN cable length
- ▶ Easy configuration with Plug and Play high speed USB 2.0 connection
- ▶ SmartLF All-in-One Scan and Copy software included
- ▶ Affordable, professional value for money!

The SmartLF Gx+ range is the first true 1200dpi optical resolution CCD scanner. It combines the benefits of new, instant-on LED lighting - lower energy requirements, a longer life and reduced environmental impact - with the superior color imaging attributes of CCD technology. In one uniquely versatile system, you get both the AEC, CAD and GIS users' need for sharply defined line detail in technical documents and maps combined with the highly accurate color reproduction and copying demanded by graphics professionals.

Colortrac's 6th generation SmartLF Gx+ 42 range now defines a new industry benchmark. Its combination of instant-on, long-life 2D LED illumination, full 1200dpi optical CCD resolution, power-saving ENERGY STAR compliance and fast scan speeds is unavailable in any other product. Importantly, the SmartLF is the only scanner with "scan once" software that works in real-time without a need to rescan, saving you time and money, making you more productive.... making the attractively-priced SmartLF Gx+ 42 range the best-of-breed in CCD-based scanning.



Colortrac
Our Business is Your Image

SmartLF Gx+ 42

Professional SmartLF Scanning Solutions for REPROGRAPHICS | COPYSHOPS | GRAPHICS DESIGNERS | MAPPING & GIS PROFESSIONALS | AEC CAD DRAWING OFFICES

**Because you need large format scanning solutions that work for you:**

- ▶ Gx+ 42 scans technical documents sharply and color graphics superbly
- ▶ Unrivalled image capture displays a full color gamut with shadows and highlights
- ▶ Has full compatibility with wide format printers through standard Windows drivers
- ▶ Optional ScanWorks³ has "the best" interactive 2D image restoration for reclaiming image detail
- ▶ Optional CopySmart provides easy, high definition professional color scan and print productivity
- ▶ CopySmart's professional color management controls ensure top quality color copies every time



Specification	Gx+ 42m/Gx+T42m mono/grayscale	Gx+ 42c/Gx+T42c +Color	Gx+ 42e/Gx+T42e +Express Color
UPGRADEABLE Note: No upgrade available from Gx+ to Gx+T models	m → c m → e	c → e	N/A
OPTICAL RESOLUTION	1200 dpi	1200 dpi	1200 dpi
INTERPOLATED RESOLUTION	9600 dpi	9600 dpi	9600 dpi
MAX SCAN WIDTH	42" (106.7cm)	42" (106.7cm)	42" (106.7cm)
MAX MEDIA WIDTH	46" (116.8cm)	46" (116.8cm)	46" (116.8cm)
MAX MEDIA THICKNESS	0.08" (2mm)/0.8" (20mm)	0.08" (2mm)/0.8" (20mm)	0.08" (2mm)/0.8" (20mm)
ACCURACY	+/-0.1% +/-1 pixel	+/-0.1% +/-1 pixel	+/-0.1% +/-1 pixel
DATA CAPTURE (COLOR/GRAYSACLE)	16-bit	48-bit/16-bit	48-bit/16-bit
COLOR SPACE	N/A	RAW RGB/sRGB	RAW RGB/sRGB
SCAN SPEED 1-BIT MONO (in/sec) @200 dpi	12.00	12.00	12.00
SCAN SPEED 24-BIT COLOR (in/sec) @200 dpi	N/A	1.00	4.00
PAPER PATH	Face-down, front entry, rear exit		
INTERFACE	High Speed USB 2.0/Gigabit Ethernet - network ready		
POWER REQUIREMENTS	External power supply 100~250 VAC autosensing +/-10% Less than 40VA (scanning) 4.2 VA (standby)		
WEIGHT & DIMENSIONS (WxHxD)	97lbs (44kg)	56.7 x 7 x 14.6" (144 x 18 x 37cm)	
HOST PLATFORM	Windows XP, Windows Vista -32-bit and 64-bit architectures		
CERTIFICATIONS	CB, CE, FCC, UL, RoHS. ENERGY STAR [®] .		
INCLUDED SOFTWARE	SmartLF All-in-One scan and copy software -supports TIFF, JPEG, PNG & PDF; WIA/STI interface.		
OPTIONAL SOFTWARE	ScanWorks - industry leading scanning software; CopySmart professional scan-to-copy software.		

¹Unlike fluorescent tubes, LEDs only come on when scanning. They have an estimated working-life of 50,000 hours or 6 years scanning 24/7. ²CCD (Charge Coupled Device).

³Colortrac scanning software - "a joy... provides the best results" Cadalyst (April 2007). For an explanation of scanning terms, see www.colortrac.com/glossary.htm

[1. Media wider than 43in (109.2cm) may exhibit some degradation in the image.] [2. The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB2 or Ethernet i/f and are not guaranteed for all media types.] [3. The achieved scan accuracy may vary depending on the operating environment and the type and thickness of media. Colortrac measures accuracy by scanning a paper original printed with a 88.58cm (27in) square target. The pixel co-ordinates of the corner points of the target image are measured and compared with the known dimensions of the original. SmartLF Gx+ scanners are tested at 20°C +/- 3°C, 60% +/- 10% RH non-condensing.] [4. The maximum resolution and size selectable for an image is limited by the file format specified, the available disk space and the computer operating system.] [5. 16 color RGB (4-bit) adaptive indexed palette images are a feature of the optional Colortrac ScanWorks software.] [6. Languages supported: Arabic, Chinese (Traditional), English, French, German, Italian, Japanese, Korean, Portuguese, Russian, Spanish.] [7. Microsoft WIA / STI is specified for the USB interface only.] [Colortrac recommends Intel Pentium, Core Duo, Core 2 Duo, HT (Hyper-Threading) and AMD Athlon Dual Core processors, at least 1GB RAM, Gigabit Ethernet, USB2 and Windows™ XP Home, Windows™ XP Professional or Windows™ Vista operating systems. SmartLF drivers support 32-bit and 64-bit processor architectures. Contact your supplier for advice on the optimum system configuration for your application.] [Colortrac SmartLF Gx+ scanners comply with ENERGY STAR, CB, CE, FCC, UL and RoHS standards and regulations.] Colortrac Ltd makes no warranty of any kind with respect to the information contained in this document and reserves the right to change specifications without notice. Colortrac and Smart LF® are trademarks of Colortrac Ltd. All other trademarks are the property of their respective owners. Copyright © 2009 Colortrac Ltd. COLORTRAC SMARTLF WIDE FORMAT SCANNERS ARE DESIGNED AND MANUFACTURED BY COLORTRAC.

COLORTRAC LIMITED
COLORTRAC HQ AND FACTORY
3-5 Brunel Court
Burrell Road
St Ives, Cambs
PE27 3LW, UK
Tel: +44 1480 464618
Fax: +44 1480 464620
info@colortrac.com

COLORTRAC INC
17301 West Colfax Avenue
Suite 165
Golden, Colorado 80401
USA
Tel: +1 303 973 6722
Fax: +1 303 973 7092

COLORTRAC LTD BEIJING
Room 4-B1B, Building No. 7, Section 3, Century City
HaiDian District, Beijing 100089, P.R. China
Tel: +86 1051 988928 Fax: +86 1051 988927

www.colortrac.com



Colortrac
Our Business is Your Image

The SmartLF Gx+ 42 & Gx+ T42 (thick media) scanner models are available in three performance levels with features optimized for different applications. If your requirements change, the m and c models can be upgraded on-site at your premises quickly and easily using our simple scanner upgrade process via email.

● standard ○ optional - not supported

Feature	SmartLF Gx+ 42 / Gx+ T42 wide format scanner model:	m	c	e
Maximum image width	42in (106.7cm) Image length: not limited by scanner	●	●	●
Maximum media width ¹	46in (117cm) Thickness: Gx+ 0.08in (2mm) / Gx+ T 0.8in (20mm)	● / ○	● / ○	● / ○
Scan speeds ² in/sec	24-bit RGB color @ 200dpi 8-bit grayscale & monochrome @ 200dpi	- 12.00	1.00 12.00	4.00 12.00
Scan accuracy ³	+/-0.1% +/-1 pixel	●	●	●
Optical resolution	Dots per inch (dpi) (User selection of 1200x1200 or 600x600 modes)	1200	1200	1200
Extended resolution ⁴	Linear interpolation from 100 to 9600dpi in 1 dpi steps	9600	9600	9600
Scan modes	16.7 million color RGB (24-bit) 256 & 16 color RGB adaptive indexed color palette (8-bit & 4-bit) ⁵ 256 level grayscale (8-bit) Black & White (1-bit)	- - ● ●	● ● ● ●	● ● ● ●
Digital image processing (Colortrac software options provide a comprehensive range of post scan image processing filters and tools)	2D Intelligent Adaptive Thresholding (IAT) (1-bit mode) Fixed Threshold Black & White (1-bit mode) Dynamic Normalization Application (DNA) with 16-bit super sampled data	● ● ●	● ● ●	● ● ●
Color Space	Normalized / linearized RAW RGB or sRGB	-	●	●
Color image processing	Gamma, brightness, black & white point adjustment	-	●	●
Advanced 2+3 wheel-drive	Dual precision ground drive rollers	●	●	●
Active Paper Transport (APT)	Dual all-wheel-drive contour rollers with high grip rubber tyres Single media hold down roller optimized for superior L/R stitch Face down, front loading, rear exit media path with side or centre justification Automatic media size detection with reliable optical media sensors	● ● ● ●	● ● ● ●	● ● ● ●
Motorized Thick Media adjustment (MTM) (Gx+ T range)	Adapts the APT for media up to 20mm (0.8in) thick Automatic detection of optimum grip roller pressure Simple operation from scanner control panel at the touch of a button	○ ○ ○	○ ○ ○	○ ○ ○
All digital image sensor technology	6 x quadri-linear CCDs each with 10,800 pixels (RGB + monochrome) Rigid monocoque chassis provides accurate camera positioning & location 48-bit primary point color image capture 16-bit primary point grayscale image capture Panchromatic monochrome and black & white	● ● - ● ●	● ● ● ● ●	● ● ● ● ●
Light source	Dual 2D extra long-life LED light system for optimum object illumination and instant-on scanning capability	●	●	●
Optics	6 x micro lens with integral infra red filter	●	●	●
User status & one touch operation	LCD scanner control panel provides easy walk up operation and user selection of scanner mode with stop, forward, rewind, scan & copy buttons User selectable IP address, local language options and panel overlay ⁶ MTM control buttons (Gx+ T range)	● ● ○	● ● ○	● ● ○
Scanner maintenance and user replaceable parts	Customer installable, plug 'n' play scanner Precision media calibration with DNA 16-bit super sampled data Automatic digital stitch adjustment / Easy access for cleaning Chemically treated, scratch resistant scan glass with magnetic mounts	● ● ● ●	● ● ● ●	● ● ● ●
SmartLF All-in-One software (included)	Scan_to_file with real-time image viewer Scan_to_copy with real-time image viewer Scan_to_email with real-time image viewer Drivers, TIFF, JPEG, PNG, PDF file formats	● ● ● ●	● ● ● ●	● ● ● ●
Interface (included)	Gigabit ethernet (2m) & USB2 (2m) data cables / local power cable Windows Image Acquisition (WIA) / Still Image Interface (STI) ⁷	● ●	● ●	● ●
Dimensions & weight	56.7in wide x 7in high x 14.6in deep (144 x 18 x 37cm) 97Lbs (44kg)	●	●	●
Power requirements	External power supply 100~250 VAC autosensing +/-10%, 50~60Hz Scanner power consumption 72Wh (scanning) 4.5Wh (standby)	● ●	● ●	● ●
Environmental impact	ENERGY STAR and RoHS compliant	●	●	●
Operating conditions	10°C - 35°C, 35% - 80% RH non-condensing	●	●	●
Scan software	ScanWorks ~ professional scan_to_archive & post scan image processing	○	○	○
Copy software	CopySmart ~ professional scan_to_print with IT8 color matching	○	○	○
EDC software	ISIS™ driver ~ connect seamlessly to EDM systems & database	○	○	○
Scanner accessories	Floor Stand 32.3in high x 21.7in deep (82 x 55cm) 29Lbs (13kg) Paper catch basket (floor stand is required) PC & LCD monitor mounting kit (floor stand is required) Universal repro stand with PC & LCD monitor mounting kit 72in wide x 53.5in high (max incl. scanner) x 31.5in deep (183 x 136 x 80cm) 99Lbs (45kg), max permissible printer height 45.5in (115.5cm)	○ ○ ○ ○ ○ ○ ○	○ ○ ○ ○ ○ ○ ○	○ ○ ○ ○ ○ ○ ○

[1 Media wider than 43in (109.2cm) may exhibit some degradation in the image.] [2 The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB2 or ethernet i/f and are not guaranteed for all media types.] [3 The achieved scan accuracy may vary depending on the operating environment and the type & thickness of media. Colortrac measures accuracy by scanning a paper original printed with a 68.58cm (27in) square target. The pixel co-ordinates of the corner points of the target image are measured and compared with the known dimensions of the original. SmartLF Gx+ scanners are tested at 20°C +/- 3°C, 60% +/- 10% RH non-condensing.] [4 The maximum resolution & size selectable for an image is limited by the file format specified, the available disk space & the computer operating system.] [5 16 colour RGB (4-bit) adaptive indexed palette images are a feature of the optional Colortrac ScanWorks software.] [6 Languages supported: Arabic, Chinese (Traditional), English, French, German, Italian, Japanese, Korean, Portuguese, Russian, Spanish.] [7 Microsoft WIA / STI is specified for the USB interface only.] [Colortrac recommends Intel Pentium, Core Duo, Core 2 Duo, HT (Hyper-Threading) and AMD Athlon Dual Core processors, at least 1GB RAM, Gigabit ethernet, USB2 and Windows™ XP Home, Windows™ XP Professional or Windows™ Vista operating systems. SmartLF drivers support 32-bit and 64-bit processor architectures. Contact your supplier for advice on the optimum system configuration for your application.] [Colortrac SmartLF Gx+ scanners comply with ENERGY STAR, CE, FCC, UL and RoHS standards and regulations.] Colortrac Ltd makes no warranty of any kind with respect to the information contained in this document and reserves the right to change specifications without notice. Colortrac and SmartLF® are trademarks of Colortrac Ltd. All other trademarks are the property of their respective owners. Copyright © 2009 Colortrac Ltd. Colortrac SmartLF wide format scanners are designed and manufactured by Colortrac Ltd.